

PRODUCT: **Aquamine 402**

DESCRIPTION:

Aquamine 402 is a blended liquid treatment formulated to control low pH corrosion (grooving) in condensate recovery systems. This product has a relatively low distribution ratio and is best suited to applications with relatively short steam distribution and condensate recovery systems.

SPECIFICATIONS:

Specific Gravity: 1.0
Colour:..... Clear Colourless Liquid
pH:..... 12.5
Odour: Strong Amine

APPLICATION AND CONTROL:

Aquamine 402 can be fed neat as received or diluted with soft water to any convenient strength. Aquamine 402 is compatible with most boiler treatment chemicals and can normally be added in a common mix tank. Treatment additions should be continuous proportionate to make-up or feedwater. Feed rates will vary depending on feedwater quality. Sufficient treatment should be added to maintain a mildly alkaline pH in all portions of the condensate system. Avoid overfeed as this product can combine with some dissolved gasses to form solid matter. Aquamine 402 is approved for use in registered establishments.

PACKAGING:

20 Kg..... Pails
205 Kg..... Drums
1000 Kg..... Totes

PRECAUTIONS:

- Avoid all contact with skin, eyes and clothing.
- Wear gloves, safety goggles/face shield and other protective clothing.
- Avoid excessive inhalation of vapours.
- Consult M.S.D.S. and product label for additional information before handling.