

**PRODUCT: Aquasolv 700**

**DESCRIPTION:**

Aquasolv 700 is a concentrated caustic based liquid cleaner formulated to remove oil, grease and particulates in new and retrofit steam boilers prior to operation. Aquasolv 700 is suitable for all steam applications where rapid boiling will ensure total contact and provide some scouring action. Aquasolv 700 is formulated to be 3-5 times more effective than standard alkaline cleaners in removing oil and grease preservatives as well as metal oxides and particulates. Cleaning times of 4-6 hours are normally adequate.

**SPECIFICATIONS:**

Specific Gravity: ..... 1.2  
Colour:..... Clear yellow liquid  
pH (1% sol'n): ..... 13+  
Odour: ..... Ethereal

**APPLICATION AND CONTROL:**

Aquasolv 700 should be added to the system at a rate of 2-5% based on boiler operating capacity. The boiler should be fired for a minimum of 4 hours, not to exceed 8 hours. Isolation of yellow metals is not required. Consult your service representative for more specific instructions.

**PACKAGING:**

24 Kg..... Pails  
246 Kg..... Drums  
1200 Kg..... Totes

**PRECAUTIONS:**

- Caution - Strong Alkaline Material (Contains Caustic Soda).
- Avoid contact with eyes, skin or clothing.
- Wear rubber gloves, goggles, rubber boots, apron, and other protective clothing.
- Consult label and MSDS for additional information.
- Do not freeze.