

**PRODUCT: Aquasolv 701**

**DESCRIPTION:**

Aquasolv 701 is a blended alkaline liquid cleaner formulated to remove oil, grease and particulates in new installations prior to operation. Aquasolv 701 is suitable for all non-steam applications where rapid circulation will ensure total contact and provide some scouring action. Performance will be enhanced if the cleaning solution can be heated to 120 - 140° F.

**SPECIFICATIONS:**

Specific Gravity:..... 1.04  
Colour:..... Yellow to Brown Liquid  
pH:..... 12.5-13.5  
Odour: ..... Bland

**APPLICATION AND CONTROL:**

Aquasolv 701 should be added to the system at a rate of 1-5% based on total system volume. The cleaning solution (heated if possible) should be circulated for a minimum of 12 hours, not to exceed 3 days. Although Aquasolv 701 is essentially a low foaming product, foam may develop in some applications which can be controlled by the addition of an antifoam. The pH of the circulating solution should be checked periodically and maintained above pH 11.0. For more specific instruction please consult your sales representative.

**PACKAGING:**

21 Kg ..... Pails  
218 Kg..... Drums  
1040 Kg..... Totes

**PRECAUTIONS:**

- Caution - Alkaline Material.
- Avoid Contact with eyes, skin or clothing.
- Do not take internally.
- Consult Label and MSDS for additional information.
- Do not freeze.