

**PRODUCT:                   Aquasolve 702**

**DESCRIPTION:**

Aquasolve 702 is a blended Neutral pH cleaner formulated to remove oil, grease and particulates in new or retrofit installations, prior to operation. Aquasolve 702 is designed for use in non-steam installations where rapid circulation will ensure good contact and provide some scouring action. Performance will be enhanced if the cleaning solution can be heated to 120° - 140° F. Aquasolve 702 is biodegradable, environmentally friendly and is safe for all metallurgies at use concentrations.

**SPECIFICATIONS:**

Specific Gravity: .....1.06  
Colour:.....Clear yellow liquid.  
Odour: .....Mild, aromatic.  
pH (concentrate):.....4.5

**APPLICATION AND CONTROL:**

Aquasolve 702 should be added to the system at a rate of 1-2% based on the total system volume. The cleaning solution (heated if possible) should be circulated for a minimum of 12 hours, not to exceed three days. Although Aquasolve 702 is essentially a low foaming product, foam may develop in some applications which can be controlled by the addition of an antifoam. For more specific instruction please consult your sales representative.

**PACKAGING:**

21 kg..... Pails  
218 kg..... Drums  
1060 kg..... Totes

**PRECAUTIONS:**

- Avoid contact with skin, eyes and clothing.
- Wear protective gloves and face shield when handling
- Consult Label & MSDS for additional information.
- Do not freeze.