PRODUCT: **Aquasolv 750**

DESCRIPTION:

Aquasolv 750 is a blended virtually neutral cleaner based on neutralized citric acid. Aquasolv 750 contains effective inhibitors for steel and copper as well as foam suppressant and a dispersant - penetrant to assist in removal and dispersion of unreactive portions of deposits. Aquasolv 750 is particularly effective in closed loop applications where deposits contain a significant percentage of iron oxides.

SPECIFICATIONS:

Specific Gravity: 1.22
Colour:..... Light Brown
pH:..... <4.0
Odour: ..... Slight ammonia

APPLICATION AND CONTROL:

Aquasolv 750 is designed for use in closed loop or open systems where primarily iron oxide deposit removal is required. The amount of Aquasolv 750 required will depend on the system volume, the amount and composition of the deposit, and the time available for the cleaning process. Normally we suggest working strengths of 1-5%. As with most cleaners, heating the cleaning solution will accelerate the removal process.

PACKAGING:

24 Kg ..... Pails
246 Kg..... Drums
1220 Kg..... Totes

PRECAUTIONS:

- Corrosive liquid.
- Avoid contact with skin, eyes, and clothing.
- Wear protective gloves and a face shield when handling.
- Consult M.S.D.S. and product label before handling.

1 Yonge Street, Suite 1801,
Toronto, ON M5E 1W7
P: | 416-452-3124
W: | alliancewatergroup.com