PRODUCT: **Aquatower 190**

DESCRIPTION:

Aquatower 190 is a concentrated synergistic blend of corrosion inhibitors formulated to rapidly pre-film primarily galvanized open recirculating evaporative cooling systems. Aquatower 190 offers corrosion protection to all system metallurgies and followed by an adequate treatment program will ensure corrosion free metal surfaces. Aquatower 190 is a blend of phosphonate, molybdate, azole and other inhibitors, which interact to stop corrosion before it starts.

SPECIFICATIONS:

Specific Gravity: 1.17
Colour:..... Clear Yellow Liquid
pH:..... >13
Odour: ..... Musty Odour

APPLICATION AND CONTROL:

Aquatower 190 can be fed neat from the container as received, or diluted as required with softened or demineralized water. Ideally feed should be proportionate to make-up via metered pump injection. Feed rates will vary depending on system type and allowable operating cycles. Circulating water concentration should be carried at 1000-2000 ppm Aquatower 190 depending on time available for pre-film. Control is normally by Moly test, which should be carried between 40-80 ppm.

PACKAGING:

23 Kg..... Pails
240 Kg..... Drums
1170 Kg..... Totes

PRECAUTIONS:

- Avoid contact with skin, eyes and clothing.
- For industrial, institutional and commercial use only.
- Not for use in potable water systems.
- Consult M.S.D.S. and product label for additional information before handling.
- Do not freeze.

1 Yonge Street, Suite 1801,
Toronto, ON M5E 1W7
P: | 416-452-3124
W: | alliancewatergroup.com