**PRODUCT:** **Aquatrol 300**

**DESCRIPTION:**

Aquatrol 300 is a blended liquid treatment formulated to control solids deposition and scale formation in low and medium pressure boilers. In many applications continued use of Aquatrol 300 will also effectively remove existing deposits. Aquatrol 300 contains organic dispersants, sludge conditioners, sequestrants, anti-precipitants, yellow metal inhibitor and an anti-foam.

**SPECIFICATIONS:**

Specific Gravity: ..... 1.04-1.05
Colour:..... Clear pale yellow
pH:..... 12.0-13.0
Odour: ..... Faint Aromatic

**APPLICATION AND CONTROL:**

Aquatrol 300 can be fed neat as received or diluted with soft water to any convenient strength. Aquatrol 300 is compatible with most boiler treatment chemicals and can normally be added to a common mix tank. Aquatrol 300 should be added continuously proportionate to make-up or feedwater. Feed rate will vary depending on boiler design, boiler cleanliness, and feedwater quality. Aquatrol 300 is approved for use in registered establishments.

**PACKAGING:**

21 Kg..... Pails
220 Kg..... Drums
1050 Kg..... Totes

**PRECAUTIONS:**

- Avoid contact with skin, eyes and clothing.
- Not for use in potable water systems.
- Consult M.S.D.S. and product label for additional information before handling.



1 Yonge Street, Suite 1801,
Toronto, ON M5E 1W7
P: | 416-452-3124
W: | alliancewatergroup.com