

PRODUCT: Aquatrol 327

DESCRIPTION:

Aquatrol 327 is a concentrated blended liquid one drum treatment incorporating new generation metal passivation technology. Aquatrol 327 is designed for use in all steam boilers operating up to 600 psi where condensate system protection is not required. Aquatrol 327 is recommended for use in systems with good quality soft water, R.O., or deionized water make up. Best results are obtained at elevated feedwater temperatures.

SPECIFICATIONS:

Specific Gravity: 1.25 – 1.30
Colour:..... Clear yellow liquid
Odour: Bland Odour
pH:..... 6.5 – 7.5

APPLICATION AND CONTROL:

Aquatrol 327 can be fed neat as received or diluted with good quality water to any convenient strength. Aquatrol 327 is compatible with most other boiler treatment chemicals and can normally be added to a common mix tank. Feed rates will vary depending on boiler design and feedwater temperature. Where practical, Aquatrol 327 should be fed to the de-aerator, storage section, condensate receiver (hotwell), or any location before the boiler feed pumps. Aquatrol 327 should be fed continuously, proportionate to make-up or feedwater. Sufficient treatment should be used to achieve excess sulfite levels specified by your service provider. Aquatrol 327 has an equivalent sodium sulfite concentration of 27%.

PACKAGING:

26 Kg..... Pails
265 Kg..... Drums
1300 Kg..... Totes

PRECAUTIONS:

- Avoid contact with skin, eyes and clothing.
- Do not freeze.
- Consult M.S.D.S. and product label before handling.