

PRODUCT: **Aquatrol 332**

DESCRIPTION:

Aquatrol 332 is a blended liquid treatment formulated to control solids deposition and scale formation in low and medium pressure boilers on soft water makeup. In many applications continued use of Aquatrol 332 will also effectively remove existing deposits. Aquatrol 332 contains organic dispersants, sludge conditioners, sequestrants, and anti-precipitants.

SPECIFICATIONS:

Specific Gravity: 1.10
Colour:..... Clear Yellow Liquid
pH:..... 12.0
Odour: Faint Ammonia

APPLICATION AND CONTROL:

Aquatrol 332 can be fed neat as received or diluted with soft water to any convenient strength. Aquatrol 332 is compatible with most boiler treatment chemicals and can normally be added to a common mix tank. Aquatrol 332 should be added continuously proportionate to make-up or feedwater. Feed rate will vary depending on boiler design, boiler cleanliness, and feedwater quality. Aquatrol 332 is approved for use in registered establishments.

PACKAGING:

22 Kg..... Pails
226 Kg..... Drums
1100 Kg..... Totes

PRECAUTIONS:

- Avoid contact with skin, eyes and clothing.
- Not for use in potable water systems.
- Consult M.S.D.S. and product label for additional information before handling.